

Timber Decking Oil

PS5300001

Intended uses

To enhance the appearance of timber decking and improve water repellancy. Can also be used to revitalise previously stained decking.

Product description

A natural oil based material in white spirit for protection of exterior timber decking

Product information

Product reference	PS5300001
Volume solids	25%
Typical thickness	Material penetrates the timber
Theoretical coverage	10 square metres per litre (see limitations)
Practical coverage	Reduce by up to 25%
Appearance/Colour	clear
VOC content	450g/L

Application details

Mix ratio	N/A
Method of application	Soft Bristle Brush
Thinner	Not required
Cleaner	Tor TH10 for cleaning equipment
Pot Life	N/A

Drying time

Substrate Temperature	Touch Dry	Hard Dry	Overcoating Interval	
			Minimum	Maximum
20°C	6-8 hours	24 hours	24 hours	28 days

Note: Drying/curing times will be shortened by higher temperatures and lengthened by lower temperatures. Do not apply below 5°C.

Storage and handling

Storage	Store in a safe place out of the reach of children
Pack Size	2.5 litres
Flash point	Above 32°C
Product weight	0.861
Shelf life	2 years in unopened containers

Surface preparation

Timber should be clean, dry and sound. Existing wood stain should be removed by sanding prior to application. If there is any risk from decay or insect attack the Timber should be treated with an appropriate Wood Preservative.

Limitations

Coverage will vary considerably depending on the type of timber, its moisture content and any preservative pre-treatment retention.

Due to the inherent properties of clear products the Timber Decking Oil will not provide any UV protection for the timber.

Regular maintenance and recoating will be required.

Do not apply too thickly as this will retard the drying of this product.

Safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

Minimum precautions for all paints:

1. Avoid skin and eye contact i.e. wear gloves, goggles, etc
2. Ensure good ventilation, mechanical if necessary.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

Definitions

Tolerances

All information quoted in this data sheet is subject to normal manufacturing tolerances.

Practical coverage

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

Pot Life

Applies only to two component products and refers to the time the mixture remains usable.

Disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

Updated: August 07